

SMP-S24d-OM3

SPEC SHEET

Product Description

SMP-S24d-OM3 is one of **s-24 cassette** series which is the MPO cassette genuinely designed by S-MODUL.

SMP-S24d-OM3 is mainly for MPO trunk cabling applications.

Featuring the highest density among the cassette it is made possible to be loaded up-to 6 sets in chassis of 1U by 19 inches.

The Push-Lock & Release design makes easy to install and uninstall.



Features




- Highest Density
- Easy install and disassemble
- Low insertion loss

Applications

- Trunk Cabling
- 25G to 25G , 10G to 10G Cabling

Product Specifications

- Drawings



- Optical Characteristics

Parameters	Criteria	Min.	Max.	Unit
Operating Wavelength	Multi-mode	850	1310	nm
MPO Insertion Loss		N/A	0.35	dB
Return Loss		25	N/A	dB
Operating Temperature		-10	+60	°C
Storage Temperature		-10	+60	°C
Fiber Type	OM3 Multi-mode Fiber	OM3 ISO/IEC 11801 and IEC 60793-210 Ala.2		

- Material & Color

Parts	Material	Color
MPO Adapter	PBT (Poly-butylene terephthalate)	Aqua
LC Adapter	PC (Polycarbonate) Sleeve : Ceramics	Aqua
Cassette Body	ABS (acrylonitrile butadiene styrene copolymer)	Black: PANTON Black C
Cassette Latch	POM (polyacetal)	Acetal Black

6 sets of s-eight in SMP-FDF-AI

